



Rhein-Ruhr Feuerstätten Prüfstelle

**Rhein-Ruhr Feuerstätten Prüfstelle • Am Technologiepark 1 • 45307 Essen**

- ❖ State recognized testing laboratory, registered no. NRW 15 in accordance with construction supervision directives
- ❖ Recognized testing laboratory in construction supervision licensing procedures
- ❖ Recognized DIN CERTCO testing laboratory, registered no. PL 139
- ❖ European Commission recognized testing laboratory, registered no. 1625

## Test report No. RRF- 29 06 1106

Test method	This appliance was tested in accordance with DIN EN 13229 and additional to the requirements of BStV of Munich and Regensburg and according to the program of certification to DINplus and the completion of Art. 15a B-VG
Test objekt:	Insets Lina 4545, 4551, 4557 Lina TV 4545, TV 4551, TV 4557, Lina 4545h, 4551h, 4557h, Lina TV 4545h, TV 4551h, TV 4557h, Lina 4580h, TV 4580h
Type:	Designation type A (multiple use not permitted) Designation type B (multiple use permitted)
Initiator:	<b>Schmid Feuerungstechnik GmbH &amp; Co. KG,</b> Gewerbepark 18, 49143 Bissendorf
Nominal heat output:	7,0 kW
Short summary of the test object	Insets made of sheet steel with fireclay firebox, window pane in the optionally self-closing firebox door, grate, ash pan, primary and secondary air supply.
Test result:	The CO-content in the flue gas for this appliance tested at nominal heat output by DIN EN 13229 with beech logs is $\leq 0,12$ Vol.-%, related to 13 % O <sub>2</sub> (equivalent 1500 mg/m <sup>3</sup> ). The dust emission in the flue gas is under these conditions is < 75 mg/m <sup>3</sup> , the NO <sub>x</sub> -content is $\leq 200$ mg/m <sup>3</sup> , the C <sub>n</sub> H <sub>m</sub> -content is $\leq 120$ mg/m <sup>3</sup> , with beech Logs related to 13 % O <sub>2</sub> The efficiency under the conditions described above is $\geq 78$ %

**Official signature of testing laboratory**

  
**Dr. Lücker**

Essen, 17.07.2007